



Capacity: 10-15 Tons

High Performance & rugged Hydraulic Mobile Dock Ramp





TECHNICAL SPECIFICATIONS

Mobile Dock Ramp	Model		MDR 10	MDR 15
Capacity		Kg	10000	15000
Working Height Range		mm	1000-1600	1000-1600
Platform Size	А	mm	7500	7500
Standing Platform	В	mm	3000	3000
Lowered Lip	С	mm	1500	1500
Length of Lip Extension	D	mm	400	400
Overall Length	E	mm	12400	12400
Service Width of Lip	F	mm	2000	2000
Overall Width Platform	G	mm	2100	2100
Lowered Height of Platform	Н	mm	1000	1000
Raised Height	I	mm	600	600
Overall Raised Height	J	mm	1600	1600

Convenience & Efficiency

- Quick avoid demurrage by loading / unloading of truck/container
- Supported by heavy duty I-beams for superior strength.
- Built to withstand frequent usage.
- · Bar grate decking for optimal traction.
- Includes quick move adapter to hook up and move ramp. Whereever required for use/parking



Safety First

- Safer environment for forklift drivers and other personnel.
- Superior traction to avoid accidents.

- Reduced workplace injuries.
- Safety chain for secure ramp-to-trailer connection.

Quality Assurance

- Designed by professional engineers to meet or exceed all stated capacities
- All products are made from 100% welded steel.
- Robust built to with stand frequent usage.

Low Maintenance

Maintenance-free design eliminates downtime.

Designed for fast installation.

Features

- Fully supported on adjustable legs
- User-friendly, two-speed hand crank system to adjust deck height
- Coated with high quality enamel paint in the colour of your choice

Options

- Hand Rails increase safety
- Dock Levellers adjust height of loading dock
- Channel Rails increase height and strength of side rail.





MARKETING H.Q. Action Construction Equipment Ltd. 4th Floor, Pinnacle, Surajkund, NCR-121009

Ph.:+91-129-4550000, Fax:+91-129-4550022 E-mail: whe@ace-cranes.com, forklifts@ace-cranes.com